



Struktol Company of America

201 E. Steels Corners Road • P. O. Box 1649
Stow, Ohio 44224-0649 • www.struktol.com
Phone (330) 928-5188 • Fax (330) 928-8726

TECHNICAL DATA

STRUKTOL[®] TPW 012

PROCESSING ADDITIVE

COMPOSITION

An optimized blend of special oleo chemicals and waxes.

TYPICAL PROPERTIES

Appearance	Beige to light tan pastilles
Dropping Point (°C)	93 - 123
Specific Gravity	0.98
Physiological Behavior	Refer to safety data sheet
Storage Stability	At least 2 years under normal storage conditions
Packaging	55 lb. bag

RECOMMENDATIONS FOR APPLICATION

STRUKTOL[®] TPW 012 is a formulated blend of lubricants designed to provide optimum processing, surface and physical property characteristics of rigid PVC compounds.

STRUKTOL[®] TPW 012 is recommended for wood-filled PVC and has been shown to provide significant processing and output rate benefits when compared to traditional lubricant formulations.

DOSAGE

2 – 8 parts depending on formulation and processing needs. Contact a Struktol technical service representative for more information.

(03/21/2012)ZB/rca

The information herein is believed to be reliable, but is presented without guarantee or warranty, express or implied. Nothing contained herein is to be construed as a recommendation for any use which is in violation of an existing patent.